

Linortek NETBELL® -NTG-W Wall Mounted Speaker SYSTEM

*Multi-function system, Built-In Software for Tone Generating, Events Scheduling
Over the Network , No Additional Software or Designated Computer Required*

The Key Features

- **Web-based Break Time Scheduling**

With the Netbell-NTG PA system controller, you can access, control and schedule bell/buzzer sounds or custom tones for break time alerts over the network from a standard web browser remotely, no software to install, no designated computer required.

- **Play Background Music**

Connect the amplifier to a music source (your computer or a MP3 player) to play background music, the Netbell-NTG will pause the music to signal your scheduled breaks, and then it will switch to play the background music.

- **Live & Pre-recorded Alerts**

Provide trigger controlled emergency alert messages for severe weather, or other special events with the digital inputs. By connecting a microphone to the amplifier, you can make live announcements across your facility



The Netbell-NTG-W is a network enabled, custom designed, affordable and easy to implement multi-function speaker system. It can be used to produce timed or manually triggered custom sounds to signal start and stop work, lunch breaks, shift changes, emergency alarm, service notification, as well as for background music or recordings, live announcements for Small to mid-sized schools, factories, businesses, commercial buildings, retail stores, churches.

Each Netbell-NTG-W system includes one network enabled Netbell-NTG PA system controller, one high quality amplifier, and various numbers of wall mounted speakers are available to choose from based on your facility size. All software and mounting hardware required for installation and operation are included. This is an easy to install system, all you need are speaker wires to connect the speakers to the amplifier.

The Netbell-NTG comes with tone/message generating, event scheduling hardware and software in one compact unit. It comes with 40 standard tones/messages and the capacity of adding/ recording custom tones and/or voice message over 10 hours. 16 tones/messages can be selected/activated by schedule and/or the digital inputs.

Netbell-NTG-W Technical Specifications

Netbell-NTG-W (Wall Mounted) Speaker System Technical Specifications

Model	W2	W3	W4	W5	W6	W7	W8	W9	W10
Part#	01-910-00063	01-910-00004	01-910-00083	01-910-00009	01-910-00010	01-910-00017	01-910-00018	01-910-00068	01-910-00070

Netbell-NTG PA System Tone Generator Controller

Netbell-NTG	1
Web Server	Built- In (All software located on built-in web server.)
Bell Scheduler	Up to 500 Web-Based Event Schedules (Add schedules from web browser)
Tone Duration	User Programmable for Each Schedule
Built-In Tones	40 Standard Tones
Custom Recorded Messages	Yes (Up to 10 Hours)
Relay Output(s)	2 (Connect physical bells)
Digital Inputs	4 (Use for digital sensors or push switch to trigger special events)
Audio Output	1 Stereo Line Output (30ohm)
Audio File Format	Ogg Vorbis audio format
Audio File Resolution	16bit/8bit
Audio File Rate	44.1K/22K/11K/
File Storage Size	1G

Speaker

Speaker	2	3	4	5	6	7	8	9	10
Mounting Type	Wall mounted								
Power Handling	4 Watts								
Frequency Range	50 Hz to 12 kHz								
Maximum SPL	93dB@10', 84dB@25'								
Speaker Configuration	Full-Range								

Amplifier

Amplifier	1 (20W)	1 (60W)
Power Source	110 VAC, 60 Hz	
Maximum Power Output	20W (1% THD)	60W (1% THD)
Speaker line input	70V, 100V, 4 -16 ohm	
S/N	MIC: 66 dB; AUX: 80 dB	Better than 90 dB
Maximum power consumption	40W	100W
Mounting	Tabletop	2U Rack Mount