

## Koda Web Relay Controller Technical Specifications

<b>General Information</b>		
<b>Model</b>	<b>KODA 100</b>	<b>KODA 200</b>
<b>Part#</b>	<b>01-910-00012</b>	<b>01-910-00011</b>
<b>MSRP (USD)</b>	<b>271</b>	<b>297</b>
<b>Technical Specification</b>		
<b>Web Server</b>	<b>Built- In (All Software Located on Built-in Web Server)</b>	
<b>Relay Outputs</b>	<b>2 Relays 1 FORM A 110/220V 10A</b>	<b>4 Relays 1 FORM A 48Volt Max 1A @24VDC</b>
<b>Digital Inputs</b>	<b>2 Optically Isolated and 2 Pull Down for Contact Close (Switch Selectable)</b>	
<b>Analog Inputs</b>	<b>None</b>	
<b>Built-in Temperature Sensor</b>	<b>Ambient on Board</b>	
<b>Temperature&amp;Humidity Sensor</b>	<b>External (Optional)</b>	
<b>Rechargeable Battery</b>	<b>On Board (For offline time &amp; settings keeping backup up to 7 days)</b>	
<b>Power Input</b>	<b>12VDC or POE (Power Supply Included)</b>	
<b>Enclosure</b>	<b>DIN Rail Mountable</b>	
<b>Dimensions</b>	<b>70mm x 100mm x 25mm</b>	
<b>Accessories</b>	<b>12VDC Power Supply, RJ45 Cable (1M), DIN Rail Mount Clip</b>	
<b>Working Temperature</b>	<b>From 0 to +60 Celsius</b>	
<b>Storage Temperature</b>	<b>From -40 to +125 Celsius</b>	
<b>Humidity</b>	<b>From 10% to 80% Non-condensing</b>	
<b>Supported Protocols</b>	<b>HTTP/ SMTP/SNTP</b>	